


Stripping machines



AI 02D

With a high reliability and the largest cross-sectional range on the market, these machines provide solutions to your wire-stripping needs. All of the stripping machines in the AI series are driven by an electric motor, and are capable of very precise stripping of various insulated wires. This version has a user-friendly design with the following features:

- ⇒ Electrically driven stripping machine
- ⇒ Integrated touch display with metric or US customary units
- ⇒ Precise stripping of various insulated wires
- ⇒ Variable adjustment of stripping length and pull-off length
- ⇒ Spare blade integrated (double-sided V-blades)
- ⇒ Cross-section continuously adjustable without changing tools
- ⇒ Low weight and compact build



Technische Daten Technical data	AI 02D
Abisolierbereich Stripping range	0.05 – 2.5 mm ² (AWG 30 – 14)
Abisolierlänge L Stripping length L	3 – 20 mm (0.12 – 0.79 in.)
Abzugslänge Pull-off length	3 – 20 mm (0.12 – 0.79 in.)
Einfüßlänge Infeed length	15 mm (0.59 in.) + L*
Taktzeit ca. Cycle time approx.	0.5 s
Anschluss Power supply	100 – 240/50 – 60/70 V/Hz/VA
Abmessungen (B x T x H) Dimensions (w x d x h)	190 x 295 x 190 mm (7.5 x 11.6 x 7.5 in.)
Gewicht Weight	7.5 kg (16.53 lbs.)
Bestell-Angaben Order Specifications	V10AI000812

* L = Abisolierlänge in mm
* L = stripping length in mm / in.