

## Universal Stripper – Crimper




### UNIC-LS

This electro-pneumatic stripper-crimper is designed for quick and reliable processing of loose Z+F insulated ferrules with the cross-sections in the range of 0.5 – 2.5mm<sup>2</sup> (AWG 20-14) and crimping length of 6, 8, and 10mm (0.24, 0.31, 0.39in.). Insulated Z+F ferrules for tri-rated wires (special size, "S") can also be handled.


- ⇒ Electro pneumatically driven stripping and crimping machine
- ⇒ Touch screen offers easy menu navigation and display
- ⇒ No tooling time or tool change
- ⇒ Short cycle time
- ⇒ Batch counter (reset possible)
- ⇒ Adjustable stripping unit
- ⇒ Crimp quality conforms to DIN 46228

Verarbeitbare Aderendhülsen Usable ferrules			
für lose isolierte Z+F Aderendhülsen for loose insulated Z+F ferrules			
0.5/6K	0.5/8N	0.5/10HL	0.5/8S-N
0.75/6K	0.75/8N	0.75/10HL	0.75/8S-N
1/6K	1/8N	1/10HL	1/8S-N
1.5/6K	1.5/8N	1.5/10HL	1.5/8S-N
2.08/8N	2.08/8XS-S		
2.5/8N	2.5/10HLS	2.5/8XS-S	

Technische Daten Technical data	UNIC-LS
Crimpbereich Crimping range	0.5 – 2.5 mm <sup>2</sup> (AWG 20 – 14)
Crimplänge CL Crimping length CL	6 – 10 mm (0.24 - 0.39 in.)
Einführlänge Infeed length	27 mm (1.06 in.) + CL*
Taktzeit ca. Cycle time approx.	1.5 s
Anschluss Power supply	100 – 240/50 – 60/110 V/Hz/VA
Druckluftanschluss Air pressure	5.5 bar (79.77 psi)
Abmessungen (B x T x H) Dimensions (w x d x h)	390 x 330 x 460 mm (15.4 x 13 x 18.1 in.)
Gewicht Weight	31 kg (68.34 lbs.)
Bestell-Angaben Order specifications	On Request



Standard: Trapezium



Optional: PZ3

