


Universal Stripper – Crimper




UNIC-L

This electro-pneumatic stripper-crimper is designed for rapid and reliable processing of loose piece Z+F insulated ferrules with cross-sections in the range of 0.5 – 2.5mm² (AWG 20-14) and crimping length of 8mm (0.31in.). Insulated Z+F ferrules for tri-rated wires (special size, “S”) can also be handled.


- ⇒ Electro pneumatically driven stripping and crimping machine
- ⇒ Touch screen offers easy menu navigation and display
- ⇒ No tooling time or tool change
- ⇒ Short cycle time
- ⇒ Batch counter (reset possible)
- ⇒ Adjustable stripping unit
- ⇒ Crimp quality conforms to DIN 46228



Standard: Trapezium



Optional: PZ3



Verarbeitbare Aderendhülsen Usable ferrules	
für lose isolierte Z+F Aderendhülsen for loose insulated Z+F ferrules	
0.5/8N	0.5/8S
0.75/8N	0.75/8S
1/8N	1/8S
1.5/8N	1.5/8S
2.08/8N	2.08/8XS-S
2.5/8N	2.5/8XS-S

Technische Daten Technical data	UNIC-L
Crimpbereich Crimping range	0.5 – 2.5 mm ² (AWG 20 – 14)
Crimplänge CL Crimping length CL	8 mm (0.31 in.)
Einfüßlänge Infeed length	35 mm (1.378 in.)
Taktzeit ca. Cycle time approx.	1.5 s
Anschluss Power supply	100 – 240/50 – 60/110 V/Hz/VA
Druckluftanschluss Air pressure	5.5 bar (79.77 psi)
Abmessungen (B x T x H) Dimensions (w x d x h)	390 x 330 x 460 mm (15.4 x 13 x 18.1 in.)
Gewicht Weight	31 kg (68.34 lbs.)
Bestell-Angaben Order specifications	V10AL000130