


Modular Stripper – Crimper



AM 02 C

The compact and user-friendly design of the AM 02 C makes this machine a unique and economical solution for all small wire and cable applications.

- ⇒ Electro pneumatically driven stripping & crimping machine
- ⇒ Rapid and reliable processing of loose insulated Z+F ferrules
- ⇒ Ferrules automatically fed by vibratory unit mounted on top of machine
- ⇒ Removable touch screen for easy menu navigation
- ⇒ Quick and easy tool change for different ferrule sizes and crimping length
- ⇒ New stripping system allows precise adjustment for different wire insulations
- ⇒ Crimp quality conforming to DIN 46228



Technische Daten Technical data	AM 02 C
Crimpbereich Crimping range	0.14 – 0.34 mm ² (AWG 26 – 22)
Crimplänge CL Crimping length CL	6/8 mm (0.24/0.31 in.)
Einfüßlänge Infeed length	16 mm (0.63 in.) + CL**
Taktzeit ca. Cycle time approx.	1.5 s
Anschluss Power supply	100 – 240/50 – 60/105 V/Hz/VA
Druckluftanschluss Air pressure	5.5 bar (79.77 psi)
Abmessungen (B x T x H) Dimensions (w x d x h)	410 x 280 x 390 mm (16.2 x 11.02 x 15.4 in.)
Gewicht Weight	23 kg (50.71 lbs.)
Bestell-Angaben Order specifications	Auf Anfrage On Request

* CL = Crimplänge in mm

* CL = Crimping length in mm / in.