

Modular Stripper - Crimper




AM 04

This electro-pneumatic modular stripper – crimper is designed for rapid and reliable processing of loose piece Z+F insulated ferrules. The AM 04 may be adapted by using the corresponding tools for ferrules with cross-sections in the range of 4 – 10mm² (AWG 12-8) and crimping lengths from 8 – 18mm (0.31 – 0.71in.).


Option: Quadrocrimp – tool

The stripper – crimper can be equipped with a quadrocrimp – tool, which creates a perfect 4-side quadratic crimp.

Specification of the processing ferrules, as well as the employed wires is necessary to determine the tool requirements.



Standard: Trapezium



Optional: Quadro



Technische Daten Technical data	AM 04
Crimpbereich* Crimping range*	4 – 10 mm ² (AWG 12 – 8)
Crimplänge CL Crimping length CL	8 – 18 mm / Quadro 8 – 12 mm (0.31 - 0.71 in. / Quadro 0.31 - 0.47 in.)
Einführlänge Infeed length	28 mm (1.10 in.) + CL**
Taktzeit ca. Cycle time approx.	2.5 s
Anschluss Power supply	100 – 240/50 – 60/110 V/Hz/VA
Druckluftanschluss Air pressure	5.5 bar (79.77 psi)
Abmessungen (B x T x H) Dimensions (w x d x h)	530 x 400 x 460 mm (20.9 x 15.7 x 18.1 in)
Gewicht Weight	42 kg (92.6 lbs.)
Bestell-Angaben Order specifications	On Request

* Verarbeitbar mit querschnittsabhängigen Werkzeugsätzen

* Processable with tooling kits depending on cross-sections

* CL = Crimplänge in mm

* CL = Crimping length in mm / in.