

## Crimper



### CR 03

The electropneumatic driven, easily adaptable crimper is specifically designed to process loose turned contacts. The range of 0.08 up to 2.5mm<sup>2</sup> (AWG 28 – 14) wires and contacts can be crimped. Standard is a 4/8-indent crimp corresponding to MIL 22520. Optionally, it is possible to adapt the machine for other crimpforms. Manual adjustment of the crimping-depth (by option automatically by motor). The machine can be converted for other contacts by using specific tool kits. All tools are easily replaceable. The crimping process is started by a foot switch.

#### Special Features

- ⇒ Crimp force monitor
- ⇒ Motoric adjustment of the crimping-depth
- ⇒ Other crimp forms: 4-indent, B-Crimp

#### Usable Contacts

Loose Turned Contacts

Technische Daten Technical data	CR 03
Crimpbereich Crimping range	0,08 – 2,5 mm <sup>2</sup> (AWG 28 – 14) 4 – 6 mm <sup>2</sup> (AWG 12 – 10)
Crimpform Crimping form	4/8-indent / B-Crimp
Einfüßlänge Infeed length	23 mm (0.91 in.)
Taktzeit ca. Cycle time approx.	2 s
Anschluss Power supply	100 – 240/50 – 60/135 V/Hz/VA
Druckluftanschluss Air pressure	5,5 bar (79.77 psi)
Abmessungen (B x T x H) Dimensions (w x d x h)	260 x 560 x 540 mm (10.2 x 22 x 21.3 in.)
Gewicht Weight	37 kg (81.57 lbs)
Bestell-Angaben Order specifications	On Request