




Special Crimp Press



SC 05

This electro-pneumatic benchtop crimper is equipped with a very efficient drive. The SC 05 is capable of crimping both insulated and uninsulated ferrules. The machine is started by a footswitch. The process is monitored by a microprocessor control.

- ⇒ Electro pneumatically driven crimping machine
- ⇒ Crimping lengths up to 18mm
- ⇒ Simple change of feeding funnel different sizes
- ⇒ Quadratic crimp form
- ⇒ Crimp started by foot-switch
- ⇒ Crimp quality conforms to DIN 46228



Technische Daten Technical data	SC 05
Crimpbereich Aderendhülsen Crimping range ferrules	0.34 – 4 mm ² (AWG 22 – 12)
Crimpbereich Zwilling-Aderendhülsen Crimping range twin ferrules	0.34 – 2.5 mm ² (AWG 22 – 14)
Crimplänge CL Crimping length CL	6 – 18 mm (0.24 – 0.71 in.)
Einfüßlänge Infeed length	13 mm (0.51 in.) + CL*
Taktzeit ca. Cycle time approx.	< 1.0 s
Anschluss Power supply	100 – 240/50 – 60/20 V/Hz/VA
Druckluftanschluss Air pressure	5.5 bar (79.77 psi)
Abmessungen (B x T x H) Dimensions (w x d x h)	165 x 405 x 240 mm (6.5 x 15.9 x 9.4 in.)
Gewicht Weight	11.5 kg (25.35 lbs.)
Bestell-Angaben Order specifications	V10CP000004

* CL = Crimplänge in mm

* CL = Crimping length in mm / in.