


Universal Stripper – Crimper




UNIC-GS

This electro-pneumatic stripper-crimper is designed for rapid and reliable processing of loose piece Z+F insulated ferrules on reels with cross-sections in the range of 0.5 – 2.5mm² (AWG 20-14) and crimping length of 8mm and 10mm (0.31in., 0.39in.).


- ⇒ Electro pneumatically driven stripping and crimping machine
- ⇒ Touch screen offers easy menu navigation and display
- ⇒ No tooling time or tool change
- ⇒ Short cycle time
- ⇒ Adjustable stripping unit
- ⇒ Crimp quality conforms to DIN 46228



Standard: Trapezium



Optional: PZ3



Verarbeitbare Aderendhülsen Usable ferrules			
Z+F Aderendhülsen auf Rollen for Z+F ferrules on reel			
0.5/8N	0.5/10 HL	0.5/8S-N	0.5/10S-HL
0.75/8N	0.75/10 HL	0.75/8S-N	0.75/10S-HL
1/8N	1.0/10 HL	1.0/8S-N	1.0/10S-HL
1.5/8N	1.5/10 HL	1.5/8S-N	1.5/10S-HL
2.5/8N	2.5/10 HL		

Technische Daten Technical data	UNIC-GS
Crimpbereich Crimping range	0.5 – 2.5 mm ² (AWG 20 – 14)
Crimplänge Crimping length	8 - 10 mm (0.31 - 0.39 in.)
Einfüßlänge Infeed length	27 mm (1.06 in.) + CL*
Taktzeit ca. Cycle time approx.	1.5 s
Anschluss Power supply	100 – 240/50 – 60/25 V/Hz/VA
Druckluftanschluss Air pressure	5.5 bar (79.77 psi)
Abmessungen (B x T) Dimensions	390 x 330 x 430 mm (15.4 x 13 x 16.9 in.)
Gewicht Weight	23 kg (50.71 lbs.)
Bestell-Angaben Order Specifications	On Request